Bipolar thermal-magnetic 16A with double element trim plate and 42 mm height aluminum Simon Cima

REF. **S195AS/8**



BASIC INFORMATION

FINISH

Aluminium

COMPATIBILITY

With Simon Cima Pro surface-mounted and flush-mounted wall boxes, Cima Classic flush-mounted wall boxes with a 33mm housing, adjustable and reduced-depth floor boxes, and PVC cable guide trunking.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)
6000 A

IP RATING
IP20

POWER SUPPLY (V~)
400 V~

CURRENT (A)
16 A

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TRIP CURVE
C Curve

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050150

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
753878

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.282

PRODUCT NET WEIGHT
0.282

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
118

PACKAGING WIDTH
121

PACKAGING LENGTH
264

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3769392

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.41

PACKAGING NET WEIGHT
1.41

PACKAGING WEIGHT UNIT
KGM