

Metal mini tower kit with 3 heights and 1 side with 2 double-socket outlets and 2 plates for 1 RJ45 graphite Simon 500 Cima

REF. 52516301-036



BASIC INFORMATION

DESCRIPTION

Model of mini-tower for Fastening reference 52516301-036, is part of the range of products and components The professional Simon 500 Cima series, suitable for different environments and installations work Professionals and domesticas. Kit, metal mini-tower with 3 heights And 1 side with 2 double socket-outlets with Schuko format and 2 plates for 1 RJ45 Format snap-fit Keystone I, Keystone II and Systimax. This made in material Of stainless steel, maximizing the service life of all its components. Available finishes in colour and Graphite tone, type of click-terminals connection (1 click ®) and type of Operation is by insertion. Measures 235,5 x 221 x 68 mm, suitable for fastening of Elements in different kinds of surfaces and work environments professionals.

FINISH

Metal

PACKAGING CONTENTS

Configured mini tower, metal
partition wall, ground
connection cable, screws and
installation manual

ETIM CLASS

EC001941

MATERIAL

Stainless steel

REMARKS

The frame holders include linkable parts that form blocks, allowing the electrical part to be separated from the voice and data part for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

1 side

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Standard 110, SL110, SL Tool-less, 216000 and 216005, Brand-Rex®, ADC Krone® KM8 Keystone, BeldenCDT® Giga Flex Keystone, Ersys®, General Cable®, Molex®, Panduit® Netkey, Ortronics® Clarity TechChoice Keystone, Rit® and other manufacturers with Keystone snap-fit system.

NUMBER OF CONNECTORS

2

RJ45 CONNECTORS

Not included

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST SHUTTER

Yes

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

FORMAT

Schuko

IK CLASSIFICATION

08

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP4X

LED CONSUMPTION INDICATOR (MA)

0.55

LINKABLE

Yes, using accessory included 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 120° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

6

NUMBER OF PLATES

2 voice and data plates

PLATE TYPE

Flat

RJ45 ADAPTOR MODULE

Included in voice and data plates

SNAP-FIT RJ45 PLATES

Keystone I, Keystone II and Systimax

SNAP-FIT TYPE

Keystone I, Keystone II and Systimax

NUMBER OF SOCKETS

2 double sockets for standard current circuits

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

REMOVAL OF THE FRAME

Only with tool

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing in any floor type, raised or concrete

REMOVAL OF THE PLATE

Only with tool

SCREWS REQUIRED FOR FLOOR FIXING

4

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50085-2-4:2009 + EN 50173-1:2011 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053100400

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.855

PRODUCT NET WEIGHT

1.855

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053100400

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

67

PACKAGING WIDTH

168

PACKAGING LENGTH

272

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.062

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.855

PACKAGING WEIGHT UNIT

KGM

