Downlight 703.25 NW Wide Flood IP65 Black

REF. **70325038-484**



BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
Hotel,Wet areas,Restaurants,Residential,Retail,Office,Healthcare,Education	1 unit	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP65

OPERATING TEMPERATURE RANGE (ºC)
15 - 35 ºC

POWER SUPPLY (V~)
230 V~

COLOR TEMPERATURE (K)
4000 K

CONTROL
On/Off

CRI
80

CUT OFF
No

DRIVER INCLUDED
Yes

L70 (ºC)
30,000 h at 25 °C

LIGHT BEAM APERTURE ANGLE (°)
40º

COLOR TYPE
NW

LIGHTING EFFICIENCY (LM/W)
91 lm/W

LUMENS (LM)
680 lm

LUMENS/W
680 lm/7.5 W

OPTICS
Wide Flood

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
7.5 W

SERVICE LIFE
30.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053089323

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.32

PRODUCT NET WEIGHT
0.2

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053089323

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.32

PACKAGING NET WEIGHT
0.2

PACKAGING WEIGHT UNIT
KGM