

**German socket outlet 16A 250V~ with safety device and fast terminal connection champagne Simon 31**

REF. 31464-64



## BASIC INFORMATION

### DESCRIPTION

Schuko socket outlet with safety device (as the covers include the child protection function) and quick terminal connection, in champagne colour and belonging to the series Simon 31. This socket-outlet has a current of 16 A and a voltage of 250V, in addition to a operation is by insertion. It has 2 modules and supports a section of wire 2.5 mm with a stripped 13 mm. Complies with the European standards and regulations UNE 20315-1-1: 2009, UNE 20315-1-2: 2009 and can be installed on surfaces with a temperature located between 5 and 40°C, approximately, although it 's true that can withstand extreme temperatures of -25 to 50°C, plus or minus. Its dimensions are 64x65 mm and it is manufactured with metal components with halogen-free insulation and trim metallized thermoplastic. For a correct maintenance to this realizable socket-outlet, it will only need to wipe it with a soft and dry cloth, without having to use abrasive cloths or cleaners that contain chlorine in its formula.

### FINISH

Champagne

### PACKAGING CONTENTS

Socket outlet with cover

### COMPATIBILITY

Simon 31 frames

### ETIM CLASS

EC000125

### REMARKS

The covers include a child-proof protective feature.

## TECHNICAL INFORMATION

### CABLE SECTION ADMITTED (MM)

2,5 mm

### IP RATING

IP20

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### FORMAT

Schuko

### TYPE OF MECHANISM

Insertion

### VERSION

Single

### INDICATOR FUNCTION

No

### MONOBLOCK

No

### VOLTAGE (V~)

250 V~

### CURRENT (A)

16 A

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

13

### INSTALLATION TYPE

Suitable for surface and flush mounting

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

UNE 20315-1-1:2009, UNE 20315-1-2:2009

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

UNITARY PACKAGING WIDTH  
0

UNITARY PACKAGING LENGTH  
0

UNITARY PACKAGING VOLUME  
3026595

UNITARY PACKAGING VOLUME  
UNIT  
MMQ

UNITARY PACKAGING GROSS  
WEIGHT  
0.1

PRODUCT NET WEIGHT  
0.1

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING EAN  
8421053055670

UNITS CONTAINED PACKAGING  
10

PACKAGING HEIGHT  
83

PACKAGING WIDTH  
165

PACKAGING LENGTH  
221

PACKAGING MEASUREMENT  
UNIT  
MMT

PACKAGING VOLUME  
3026595

PACKAGING VOLUME UNIT  
MMQ

PACKAGING GROSS WEIGHT  
0.995

PACKAGING NET WEIGHT  
1

PACKAGING WEIGHT UNIT  
KGM