

PD-10 PIR+US recessed box On/Off+PF white IP20

REF. 89252223-230



BASIC INFORMATION

DESCRIPTION

Presence and light detector flush-mounted PIR + US. The recommended installation height is 2.8 m, with a maximum height of 3.5 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 10 m and the radial detection range is 10 m.

The light regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The detector configuration is done through potentiometers and remote control.

It has a TEACH operating mode. Possibility of interconnection between master/master and master/slave sensors up to 10 detectors. It has two outputs (On/Off + Potential free) and the maximum switchable power is 2000 W (500 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -25 - 55 °C. White finish, protection rating IP 20 and dimensions: 120 x 120 x 66 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

2 channels (On/Off + Potential Free)

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053381953

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.331

PRODUCT NET WEIGHT

0.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053381953

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

162

PACKAGING WIDTH

100

PACKAGING LENGTH

142

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.331

PACKAGING NET WEIGHT

0.2

PACKAGING WEIGHT UNIT

KGM