Adjustable floor box for 6 double elements for installation in gray pavement Simon Cima

REF. **SF670/1**



BASIC INFORMATION

FINISH
Grey

MATERIAL
Various

COMPATIBILITY
With Simon Cima and Simon 27 Play/Simon K45 mechanisms (via adapter)

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
16

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1800kg

RAL
7011

RECESS DIMENSION (MM)
210 x 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plástica y metálica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052765

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2.15

PRODUCT NET WEIGHT
2.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052765

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
79

PACKAGING WIDTH
236

PACKAGING LENGTH
342

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
7483280

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2.22

PACKAGING NET WEIGHT
2.15

PACKAGING WEIGHT UNIT
KGM