

Surface/Suspended Luminaire 1600mm DALI White Microprismatic CRI80 3000K

REF. 86542330-683



BASIC INFORMATION

DESCRIPTION

Linear surface/suspended luminaire of 1,600mm, in white finish with microprismatic optics and excellent CRI>80 color rendering. Also available in black and in a 4000K version. With 60W of power, it delivers a luminous flux of 5.427 lm, ideal for general lighting in offices, retail spaces, corridors, or residential areas requiring uniform, high-quality light. This fixture is controlled via DALI, a system based on an international standard that ensures full compatibility between different devices through a master-slave protocol. The DALI logo indicates that the product relies on this system for its control.

Regarding its lifespan, it's worth noting that it reaches 50,000 hours (L70B10), so if kept within an average range of -20°C to +35°C, the fixture should last considerably longer, and in perfect condition. Its dimensions are 1685x50x75mm, made of aluminum with IP40 protection, suitable for indoor use.

This product has the following reference number: 86542330-683. Here you can find all its features in terms of logistics data, installation manuals, technical information, and other product details.

FINISH

White

MATERIAL

Aluminium

APPLICATION

Hotel, Restaurants, Residential, Retail

REMARKS

White linear luminaire of 1,600mm with microprismatic optics, CRI>80 3000K, and DALI dimmable system, delivering 5.427 lm for uniform, long-lasting lighting (50,000h) in any space.

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP40

OPERATING TEMPERATURE RANGE (°C)

-20...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI

COLOR TYPE

WW

OPTICS

General

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | EN IEC 60598-2-1:2021 | EN 62493:2015 | EN IEC 55015:2019 + A11:2020 | EN IEC 61547:2023 | EN IEC 61000-3-2:2019 + A1:2021 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN IEC 63000:2018 | EN 62717:2017 + A2:2019

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0

PACKAGING WIDTH

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

0

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8431715335606

PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING HEIGHT

0

PACKAGING NET WEIGHT

0