

Modular luminaire 720 Advance M4 120x30 Low Glare NW DALI

REF. 72061340-684



BASIC INFORMATION

DESCRIPTION

The luminaire 720 modular Advance M4 of the collection for indoor lighting of Simon, is the option to obtain a perfect lighting quality, respecting the environment, comprising multiple LEDs low consumption, brings a with a white tone of neutral colour temperature of 4000 K. It, and to prevent glare, has a with system LowGlare micro prismatic optics. With a luminous light flux 3400 lm for NW, and a power consumption of the luminaire 28 W, it is compatible with a voltage of 230 V AC power and 50-60 Hz. Thanks to have the latest LED technology, has a service life of 100,000 hours for the L70 at 25 ° C and 40,000 hours for the L90. Includes interface of adjustment bidirectional DALI to facilitate the control of the luminaire. With a compact design of finishes in white and an installation suitable for false ceiling, visible hardware, the luminaire 720 modular of Simon adapts to all kinds of decorative spaces and environments.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191729

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191729

PACKAGING VOLUME

0.252

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

300

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.58

PACKAGING LENGTH

1200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5