

2-way push-button switch 10AX 230V~ with fast terminal connection system gold Simon 270

REF. 20000201-095



BASIC INFORMATION

FINISH

Matt gold

TYPE OF ROCKER

Large

MATERIAL

Thermoplastic

COMPATIBILITY

Simon 270 frames

PACKAGING CONTENTS

Mechanism, cover and instruction sheet

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION No	NOMINAL VOLTAGE (V~) 230 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	CURRENT (A) 10 AX	OPERATING TEMPERATURE RANGE (°C) 5 - 45 °C
TYPE OF COVER Large	IP RATING IP20	POWER SUPPLY (V~) 230 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 1036
FORMAT Fast	TYPE OF MECHANISM Pivoting	STORAGE TEMPERATURE RANGE (°C) -25 - 75 °C
FREQUENCY 50 - 60 Hz		VOLTAGE (V~) 127/230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for flush mounting
	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053268049

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.028

PRODUCT NET WEIGHT

0.026

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053268056

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

47.75

PACKAGING WIDTH

57

PACKAGING LENGTH

262

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

713098.5

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.13

PACKAGING WEIGHT UNIT

GRM

