3RCA connector female with trim plate aluminium Simon K45

REF. **K105B/8**



BASIC INFORMATION

DESCRIPTION

Especially suitable for installation in meeting rooms, doctors mixtures, etc., the 3RCA connector, female, K45, is suitable for transmission both audio and video thanks to its 3 connectors: Red (audio right), audio yellow (left) and white or black (video). With trim plate and finished in Aluminium, it can be installed in surface-mounted or recessed, with screw terminal connection. The 3RCA connector together with the trim plate, support a maximum length of cabling 20 meters and a cable section from 0.2 to 0.5 mm Manufactured with thermoplastic materials and self-extinguishing halogen-free, protects your room of the flame spread and toxicity smoke in case of fire, reaching a maximum temperature of between -25 and 50ºC. Thanks to its 3RCA connector with trim plate, Simon K45, gives you the maximum functionality to make it work area has the best quality multimedia connections.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Female 3RCA connector, cable fixing clamp and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 20 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
RCA

NUMBER OF CONTACTS
9

NUMBER OF POSSIBLE ELEMENTS
1/2 element

FORMAT
RCA

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
9

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436064713

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.023

PRODUCT NET WEIGHT
0.023

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436064713

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
42

PACKAGING LENGTH
50

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.012

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.023

PACKAGING NET WEIGHT
0.023

PACKAGING WEIGHT UNIT
KGM