

## POINT spotlight basic Rail 2700 K Flood Black

REF. 92001022-288



### BASIC INFORMATION

#### BODY MATERIAL

Die-cast aluminium

#### PACKAGING CONTENTS

1 Unit

#### APPLICATION

Domestic,Office,Retail,Contract

#### PACKAGING DIMENSIONS (MM)

160x255x234 mm

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DIRECTIONAL

Yes

### LUMENS (LM)

1500 lm

### IP RATING

IP20

### DRIVER INCLUDED

Yes

### NUMBER OF LUMINAIRES

1

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### ELECTRICAL CLASS

III

### MACADAM STEPS

<3 Step MacAdam

### POWER SUPPLY (V~)

100/277 V~

### ENERGY EFFICIENCY

A+

### OPTICS

Flood 30°

### RAL

9005

### L70 (°C)

100000h at 25°C

### PHOTOBIOLOGICAL CLASSIFICATION

Class II

### COLOR TEMPERATURE (K)

2700 K

### L90 (°C)

40000h at 25°C

### POWER FACTOR (Φ)

> 0,98

### CONTROL

On/Off

### COLOR TYPE

WW

### POWER (W)

25 W


### CRI

90

### LIGHTING EFFICIENCY (LM/W)

88 lm/W

## PHOTOMETRY ASSETS – POLAR



## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Flush-mounted

### INSTALLATION TYPE

Rail

## REGULATIONS

### EAC MARKED

Yes

### ECORRAE MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8436547041237

### PACKAGING VOLUME

10014720

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

234

### PACKAGING GROSS WEIGHT

1.12

### UNITARY PACKAGING GROSS WEIGHT

2.38

### PACKAGING WIDTH

255

### PACKAGING NET WEIGHT

1.02

### PRODUCT NET WEIGHT

1.02

### PACKAGING LENGTH

160

### PACKAGING WEIGHT UNIT

KGM