

Modular Luminaire 720 Advance M4 120x30 NW DALI

REF. 72061340-884



BASIC INFORMATION

DESCRIPTION

Are you looking for a neutral lighting and high quality? The range of luminaires 720 of Simon is one of the best options for installation in the ceiling, offering all the guarantees of durability and efficiency of energy since it has a reduction in energy consumption of 20% with respect to the conventional luminaires. The luminaire 720 modular Advance M4 120 x 30 NW has a system of DALI control, a traslucida optics and a power of 34 Watts offering a high light output of 4100 lumens. Its stylish design and its finished in white makes it a piece that adapts perfectly to any space where it is installed. The maintenance of this piece is that requires minimum, since it is not necessary to the replacement of the lamps nor the cleaning of the luminaire, a product created to be durable and offer a light flux constant light of more than 40,000 hours.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

146 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

4100 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

4100 lm/28W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053124895

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.52

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124895

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.52

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM