

PD-7x7 PIR+LUX SR recessed DALI-2 Master white IP20

REF. 89212422-230



BASIC INFORMATION

DESCRIPTION

Flush-mounted presence and brightness detector PIR. The recommended installation height is 1.8 m, with a maximum height of 8 m. It has a detection angle of 360° and an opening angle of 100°. The tangential detection range is 7 x 7 m and the radial detection range is 5 x 5 m. The brightness regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The configuration of the detector is performed through potentiometers and remote control. It features a TEACH operating mode. Possibility of interconnection between master/master and master/slave sensors up to 10 detectors. The control protocol is DALI-2 Master. The number of dimmable luminaires through the DALI bus is 24 (2 groups). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C. White finish, protection grade IP 20 and dimensions: 120 x 120 x 113 mm. 5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP20

RAL

9010

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356548

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.29

PRODUCT NET WEIGHT

0.151

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053356548

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

90

PACKAGING LENGTH

142

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1278000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.29

PACKAGING NET WEIGHT

0.151

PACKAGING WEIGHT UNIT

KGM