

IP66 tray leveler accessory for floor boxes in concrete

REF. KFA1003



BASIC INFORMATION

DESCRIPTION

Facilitates the installation of your watertight floor boxes with our IP66 leveling accessory for floors. This innovative accessory lifts and levels the box up to a maximum of 35mm, ensuring perfect alignment even on uneven substrates, as well as its installation on pavements up to 116.5mm thick. Its design allows for quick and simple installation, ensuring that your box is aligned with the surface of your floor without added effort. Improve the efficiency and precision in your projects with our new leveling accessory.

COMPATIBILITY

K45 Solutions

ETIM CLASS

EC002420

TECHNICAL INFORMATION

IP RATING

IP66

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401309

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.024

PRODUCT NET WEIGHT

0.022

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053402009

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

57

PACKAGING WIDTH

76

PACKAGING LENGTH

76

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

329232

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.236

PACKAGING NET WEIGHT

0.22

PACKAGING WEIGHT UNIT

KGM