Aluminium mini column with 1 side for 4 elements graphite Simon 500 Cima

REF. **52550112-033**



BASIC INFORMATION

DESCRIPTION

Anodised aluminium mini column for 1 side suitable for 4 elements with a graphite finish, this mechanism is included in the Simon 500 Cima series and measures 304 x 110 x 72 mm It is an article in compliance with the current regulations and is also suitable for installation in any type of floor. It doesn ' t matter which this is raised or concrete. Thanks to the shape of the baseboard, it is possible to integrate the mini column to the floor trunking 85x18 mm Maintenance is essential in this type of products, as this will give a greater durability. To do this, just clean the piece with a soft, dry cloth and avoid abrasive cleaners containing chlorine. The collection Simon 500 Cima is a series that aims to provide maximum workplace solutions to the work stations. This mechanism is a good example of this.

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using an adaptor)

PACKAGING CONTENTS

Mini column, baseboard, lower and upper trim, non-slip adhesive foam, fixing studs, ground connection cable, screws and installation manual

ETIM CLASS

EC001941

REMARKS

The shape of the baseboard allows integration of the mini column with the 85 x 18 mm floor trunking

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)
+120 °C

EARTHING RESISTANCE
< 0.05 Ohms

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Constant clearance between electric wiring and Voice, Data and Multimedia cables, eliminating electromagnetic interference and possible transmission errors.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-25 to +120 °C

NUMBER OF MODULES
4

VERSION
1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

TYPE OF FASTENING
Using the screws supplied

INSTALLATION DIRECTION
Vertical

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING
4

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053094358

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.26

PRODUCT NET WEIGHT
1.26

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053094358

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
85

PACKAGING WIDTH
128

PACKAGING LENGTH
867

PACKAGING MEASUREMENT UNIT
MMT


PACKAGING VOLUME
9432960


PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.26

PACKAGING WEIGHT UNIT
KGM


76
72
110


316