

Flat voice and data plate with dust cover for 2 Systimax® RJ45 connectors white Simon 75

REF. 75593-60



BASIC INFORMATION

DESCRIPTION

This voice and data plate is flat compatible with Systimax. It has 2 connectors and a dust shutter and includes an RJ45 adaptor module. This model of voice and data plate has no engraving whatsoever. The plate of voice and data flat plate with dust cover for 2 with RJ45 Systimax connectors from Simon 75 is available in 3 different finishes, but it is always recommended to choose the frame of the same colour of the plate that we select. If you decide to choose the flat data and voice plate with two connectors is an individual version, this model of flat voice and data plate includes one element but does not include signaling function or modules. The limit of the recommended temperature range is from 5 to 40°C reaching maximum temperatures of -25 to 50°C. It is suitable for installations in surface mounting or flush mounting. This flat voice and data plate does not apply regulation. The manufacturing material of the voice and data plate is thermoplastic, with a white plastic finish is recommended for maintenance use a soft cloth slightly moistened in soapy water.

FINISH

White

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Plate

SYMBOL

Without engravings

COMPATIBILITY

Simon 75 mechanisms

REMARKS

Available in 3 finishes. It is recommended to choose a frame the same colour as the selected plate.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

COMPATIBLE WITH CONNECTORS

Systimax

NUMBER OF CONNECTORS

2

DUST SHUTTER

Yes

NUMBER OF POSSIBLE ELEMENTS

1 element

FORMAT

RJ45

INDICATOR FUNCTION

No

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

PLATE TYPE

Flat

RJ45 ADAPTOR MODULE

Included

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053072578

PACKAGING VOLUME
1.518

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
5

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
82

PACKAGING GROSS WEIGHT
0.29

UNITARY PACKAGING GROSS
WEIGHT
0.058

PACKAGING WIDTH
83

PACKAGING NET WEIGHT
0.29

PRODUCT NET WEIGHT
0.058

PACKAGING LENGTH
223

PACKAGING WEIGHT UNIT
KGM