

French socket outlet 16A 250V~ with safety shutter and quick terminal connection white Simon K45

REF. KS22/9



BASIC INFORMATION

DESCRIPTION

The Simon K45 white in colour, is a French socket outlet with a current of 16 A and a voltage of 250V and also has a safety shutter and quick terminal connection. It has 2 modules and offers the possibility to order a replacement for the pin, in the event of breakage or loss. It measures 45x45x 42,3 mm and it allows a cable section of 1.5 to 2.5 mm and wire stripping of 12 mm. It has been designed according to the following standards: IEC 60884-1 ED 3.2 + UNE 20315-1-1:2009 + UNE 20315-1-2:2009 and is a socket outlet suitable for both surface and flush mounting, with temperatures between -5 and 60 °C. To clean it, you only need to wipe it with a soft, dry cloth and never use abrasive cloths or cleaners that contain any amount of chlorine.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Socket plug with trim cover and installation manual

ETIM CLASS

EC000125

REMARKS

Possibility to order replacement for pin, in the event of breakage or loss, through Art.No. AC33/6

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

AVAILABLE IN

Shucko and french format

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

French

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

LINKABLE

Yes, using accessory AC11

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2 modules

MONOBLOCK

No

RAL

9003

NUMBER OF SOCKETS

1

VERSION

Single

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

NUMBER OF TERMINALS

2 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.056

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

1212505

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053123119

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

121251

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.62

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

49

PACKAGING NET WEIGHT

0.56

UNITARY PACKAGING GROSS
WEIGHT

0.056

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

245