

Extension 1 metre for aluminium column with 2 sides oval Simon K45

REF. ALK72P10/8



BASIC INFORMATION

DESCRIPTION

To combine the most innovative design and the most intuitive functionality is possible. So at least it 's what we believe at Simon. With dimensions of 1000 x 80 x 110 mm, 1 metre extension for column in two sides oval aluminium finish is one of the products most highlights the wide catalogue of the series Simon K45. To ensure the robustness of the set, it is only possible to combine one extension per column. The structure of this extension has been designed in anodised aluminium. In what translates this? In order to have a very resistant to adverse conditions of temperature and relative humidity, as well as to deterioration by its use and oxidation that occurs over time. Also, all these qualities can be enjoyed with a suitable for all types of budgets.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

2-sided (Oval)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using connecting pins

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050556

PRODUCT NET WEIGHT

2.8

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

12051000

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050556

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.8

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

90

PACKAGING NET WEIGHT

2.8

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.8

PACKAGING LENGTH

1030