

DALI power supply LOOP Wall-mounted luminaire

REF. 98350000-199



BASIC INFORMATION

APPLICATION

Domestic, Office, Retail, Hotel, Contract Unit

PACKAGING CONTENTS

ETIM CLASS

EC002556

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

110/240 V~

ELECTRICAL CLASS

II

IP RATING

IP20

CONTROL

DALI

ENERGY EFFICIENCY

A+

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DRIVER INCLUDED

Yes

POWER FACTOR (Φ)

> 0,9

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547041916

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547041916

PACKAGING VOLUME

136500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

21

PACKAGING GROSS WEIGHT

130

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

100

PACKAGING NET WEIGHT

0.13

UNITARY PACKAGING GROSS
WEIGHT

0.14

PACKAGING LENGTH

65

PACKAGING WEIGHT UNIT

GRM

PRODUCT NET WEIGHT

0.13