

2-way switch with key 2.5A 250V~ 2 positions (key removable in both positions) and welding terminal connection white Simon 27 Play

REF. 27521-65



BASIC INFORMATION

DESCRIPTION

If what you need is to change the direction or interrupt the step of the current electrical in any circuit, this is the perfect product. It is a 2-way switch for up to 2.5 A current and 250 volts, in the Simon Play 27 series. Is a white adaptable colour. It measures 45 x 45 millimetres and is made up of two modules, the rocker operation is carried out by welding and its installation is very simple, allowing you to do it directly in surface-mounted or recessed. It is a 2-way switch that operates with a key. Simon, always thinking about users, gives it great versatility at its products that offer multiple installation possibilities, handling and operation. In this sense, this 2-way switch has a system of two positions and a key blade that can be removed in both positions. The 2-way switch is made of high quality. The trim is made of thermoplastic and its components are components with insulation and free of halogens, which extends the service life of the product.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with cover

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and key is removable in both positions.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Both positions

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VOLTAGE (V~)

250 V~

CURRENT (A)

2,5 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

CLAW

Included

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and
Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053082133

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053082133

PACKAGING VOLUME

0.329

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

57

PACKAGING GROSS WEIGHT

0.095

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

76

PACKAGING NET WEIGHT

0.095

UNITARY PACKAGING GROSS
WEIGHT

0.095

PACKAGING LENGTH

76

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.095