

LedFlex 810.33 4000 K IP65

REF. 81033100-984



BASIC INFORMATION

APPLICATION

General lighting, Indoor
decorative lighting

PACKAGING CONTENTS

1 unit (5m)

TECHNICAL INFORMATION

IP RATING

IP65

DRIVER INCLUDED

No

LUMENS (LM)

2500 lm

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

LUMENS/W

2500 lm/24W

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

PWM

COLOR TYPE

NW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

104,2 lm/W

POWER (W)

24 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053202524

PACKAGING VOLUME
1200

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
1

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
2

PACKAGING GROSS WEIGHT
409.2

UNITARY PACKAGING GROSS
WEIGHT
0.409

PACKAGING WIDTH
24

PACKAGING NET WEIGHT
0.409

PRODUCT NET WEIGHT
0.409

PACKAGING LENGTH
25

PACKAGING WEIGHT UNIT
GRM