

Downlight 725.22 Flush mount WW General 1-10V White

REF. 72522130-983



BASIC INFORMATION

DESCRIPTION

Downlight 725.22 with Series Advance General optics and for installation in recessed. Its Ecorrae is category B and features a colour temperature of 3100K and a light intensity of 2100lm / 24 W. It has a service life of a 30,000 hours, approximately, operating at 25 ° C, although it is a type of downlight perfect for installation in rooms with a temperature is between -15 and 40°C. This downlight is manufactured in aluminium with white finish and its installation is by recessed. It has a weight of 1.25 kg and dimensions of 233 x 57 mm Is controlled via 1-10 V, it has a frequency of 50 / 60 Hz and its power supply is 100-240 V. The downlights of the series 725 is ideal for creating uniform lighting with high visual comfort, especially in transit areas, corridors and also for general office lighting and commercial establishments.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2100 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

2100 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

1-10 V

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

88 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.25

PRODUCT NET WEIGHT

1.25

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116722

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

250

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4.375

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.25

PACKAGING WEIGHT UNIT

KGM