

PD-24x24 PIR+LUX BT Mesh surface On/Off white IP54

REF. 89212136-230



BASIC INFORMATION

DESCRIPTION

Surface PIR presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 24 x 24 m and the radial detection range is 9 x 9 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector configuration is done through potentiometers and a Bluetooth application.

It features a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, IP 54 protection grade and dimensions: 123 x 123 x 64 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342329

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.37

PRODUCT NET WEIGHT

0.26

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342329

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.37

PACKAGING NET WEIGHT

0.26

PACKAGING WEIGHT UNIT

KGM