

4-way switch 10A 127-220V with screw terminal connection aluminum Simon 25 Plus

REF. 25251-33



BASIC INFORMATION

FINISH

Aluminium

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

3,3 mm

CURRENT (A)

10 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)

127/220 V~

POWER SUPPLY (V~)

127/220 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY
(MM)

11

TYPE OF TERMINAL
CONNECTION - FUNCTION 1

Fast

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
22.2

UNITARY PACKAGING WIDTH
42

UNITARY PACKAGING LENGTH
41.2

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.038

UNITARY PACKAGING VOLUME
UNIT
DMQ

UNITARY PACKAGING GROSS
WEIGHT
25.11

PRODUCT NET WEIGHT
22

UNITARY PACKAGING WEIGHT
UNIT
GRM

PACKAGING EAN
7506207331518

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
45

PACKAGING WIDTH
85

PACKAGING LENGTH
224

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
0.857

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.486

PACKAGING NET WEIGHT
440

PACKAGING WEIGHT UNIT
KGM