

Adjustable intermediate feed black

REF. 89940338-039



BASIC INFORMATION

DESCRIPTION

There are countless advantages that will bring us to electrical systems, the installation of the intermediate Power adjustable in black colour. One of them is the cost savings that obtendremos thanks to the energy efficiency that lograremos in private homes, commercial premises and corporate headquarters thanks to it, all at the most competente that there are today in the sector. Its installation must be carried out on a 3-phase rail. The quality of the materials with which it has been designed to its structure has made it one of the most resistant in the event of small accidents spotlights and knocks, impacts, as well as the deterioration over time, in addition, the qualities of the same are maintained in the time even in adverse conditions of temperature and humidity by very extreme temperatures that are.

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase rail

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053192856

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053192856

PACKAGING VOLUME

9000000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

100

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

300

PACKAGING NET WEIGHT

0.04

UNITARY PACKAGING GROSS WEIGHT

0.056

PACKAGING LENGTH

300

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.04