

Adjustable floor box for 1 double element for installation in pavement floor gray Simon Cima

REF. SF170/1



BASIC INFORMATION

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With Simon Cima and Simon 27
Play/Simon K45 mechanisms (via
adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

2

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

800kg

RAL

7011

RECESS DIMENSION (MM)

170 x 115 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052635

PRODUCT NET WEIGHT

0.72

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052635

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.715

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.72

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.72

PACKAGING LENGTH

195