

IP66 Mechanism holder and security frame with schuko and RJ45 5e UTP

REF. KFH115USEC/72



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of watertight floor boxes for indoor and outdoor environments. This is a mechanism frame with a security lock for environments that require restricted access, featuring a Schuko socket and a category 5e UTP RJ45 connector. In combination with its base, it allows for installation on raised floors or pavement. The product design, combined with its manufacture in stainless steel, enables a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm² in any direction, achieving an IP66 protection rating when the lid is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal curvature radius for cabling in high-category voice and data connections. Our accessory for connection with a closed lid is also available, allowing us to keep our connections active with an IP54 rating (see reference KFA1001), the ability to level our box in case of an irregular slab (see reference KFA1003), or the capacity to concatenate multiple boxes (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 50173-1:2018 | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 |

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053332788

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053332788

PACKAGING VOLUME

1837680000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

1140

PACKAGING GROSS WEIGHT

0.449

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

1240

PACKAGING NET WEIGHT

0.352

UNITARY PACKAGING GROSS
WEIGHT

0.449

PACKAGING LENGTH

1300

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.352