


Front face kit for 3 elements with 2 2P sockets and 1 matt white 2xUSB charger Simon 100

REF. 10020321-230



BASIC INFORMATION

FINISH

Matt white

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

TYPE OF MECHANISM

Insertion

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

INSTALLATION DIRECTION

Horizontal and vertical

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

2P socket: Connection (1 click®)

TYPE OF TERMINAL CONNECTION - FUNCTION 2

USB: Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053233139

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053233139

PACKAGING VOLUME

480295.2

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

0.13

UNITARY PACKAGING GROSS
WEIGHT

0.13

PACKAGING LENGTH

226

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.13