

Angled voice and data plate with dust cover for 1 element with 2 category 5e UTP RJ45 graphite Simon 500 Cima

REF. 50004086-038



BASIC INFORMATION

DESCRIPTION

Plate of voice and data plate of the Simon 500 Cima series. The plate includes a dust shutter and has an element with two RJ45 connectors. The finished in graphite colour gives the grey plate of elegance, making it possible to its use in a multitude of spaces. This plate is part of the category 5e UTP and is manufactured from materials thermoplastically isolated, that enhance the security in its use, as it does not contain halogens, and in the case of high temperatures the smoke emission, which minimizes the toxicity. This is the individual version of the plates of this series with a single module. In addition to being able to adapt to one or two RJ45 connectors, the clips kit includes the necessary to facilitate the installation of the voice and data plate in vertical or horizontal enclosures. Its measures are 50 x 50 x 42.5 millimetres. The maintenance of the voice and data plates Simon 500 Cima only requires dry and soft cloths for cleaning, it is not advisable to use abrasive chemical with elements such as chlorine.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with
dust cover, 2 category 5e UTP
RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

26

UNITARY PACKAGING WIDTH

58

UNITARY PACKAGING LENGTH

86

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

129688

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.075

PRODUCT NET WEIGHT

0.075

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053097687

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

26

PACKAGING WIDTH

58

PACKAGING LENGTH

86

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.052

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.5

PACKAGING WEIGHT UNIT

KGM

