

Customisable kit with 2xUSB charger, 4 schuko socket outlets and 1 empty element white S400 Top

REF. 42624000-130



BASIC INFORMATION

DESCRIPTION

Simon offers a product designed for workspaces that require all connections in one place. Within the 400 series, we find this customizable tabletop kit with a 2 x USB charger, 4 schuko sockets, and an empty element for personalization in white color. This version for 6 elements has dimensions of 295 x 120 x 80 millimeters and features a manual lifting system that allows us to access it in a practical and instantaneous way. A cutting-edge product made of metal with a white finish, the trim cover is made of painted steel with a very impact-resistant anodized aluminum profile. Simon offers extra safety in the unlikely event of combustion, as its covers and fastenings prevent flame spread because they are made of self-extinguishing thermoplastic. A product created for currents of 16 amperes and a voltage of 250 volts.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

RAL

9016

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

CURRENT (A)

16 A

NUMBER OF REAR ENTRANCES

1

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

IP RATING

IP30

NUMBER OF SOCKETS

4 sockets for standard current circuit

NUMBER OF POSSIBLE ELEMENTS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF USB CHARGERS

1

FORMAT

Schuko

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

6 elements

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053273548

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

1.09

PRODUCT NET WEIGHT

1.09

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053273548

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

116

PACKAGING LENGTH

303

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3163320

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.09

PACKAGING WEIGHT UNIT

KGM