VGA HD15 female connector with trim plate white Simon K45

REF. **K100A/9**



BASIC INFORMATION

DESCRIPTION

It is a VGA HD15 female connector, which consists of a trim plate in white colour, the mechanism is equipped with a module for half element is suitable for surface and flush mounting and is included in the s erie Simon K45 presents a terminal connection system by welding and works by insertion. The manufacturer recommends that the length of the cabling does not exceed the 20 meters. If in doubt, please refer to the instruction sheet of this product. This connector measuring 22.5x45 mm and it is manufactured with metal components with thermoplastic insulation and self-extinguishing halogen-free. This material stands out for being 100% safe in case of fire, as prevents extend the fire and the low toxicity if any smoke. Although it is an article that resists very well all kinds of temperatures, the ideal thing is to install it in an environment between 5 and 40º.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

VGA HD15 female connector

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 20 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
VGA

NUMBER OF CONTACTS
15

NUMBER OF POSSIBLE ELEMENTS
1/2 element

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
9003

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
10

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
70

UNITARY PACKAGING WIDTH
93

UNITARY PACKAGING LENGTH
140

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
911.4

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.016

PRODUCT NET WEIGHT
0.016

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436045460

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911.4

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.16

PACKAGING NET WEIGHT
0.16

PACKAGING WEIGHT UNIT
KGM