

Front kit for 1 element with 1 Simon iO switch gloss white Simon 100

REF. 10020112-130



BASIC INFORMATION

DESCRIPTION

Front kit for 1 element, with 1 white Simon iO switch and glossy finish of the Simon 100 series. It operates with a 10 AX intensity and a voltage of 250 V. It has a cut type of emborning and a type of operation by push button - tilting.

It has dimensions of 85.5x83.5mm and the type of installation it allows can be both vertical and horizontal. In addition, it should be noted that, to ensure proper maintenance, a temperature range of 5 to 40° C must be preserved for operation and a temperature range of -25 to 50° C for storage. With regard to cleaning, simply pass a damp cloth and avoid abrasive products containing chlorine.

It has been done in accordance with regulations 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60669-2-1: 2004 + EN 60669-2- 1: 2004 A1: 2009 + EN 60669-2-1: 2004 A12: 2010 and is marketed in the EC.

FINISH

Gloss white

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

10 AX

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Push button rocker switch

MONOBLOCK

No

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

1 element

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for flush mounting

KIT INSTALLATION DIRECTION

Vertical and horizontal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053201404

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053201404

PACKAGING VOLUME

70560

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

10

PACKAGING GROSS WEIGHT

0.064

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

0.064

UNITARY PACKAGING GROSS
WEIGHT

0.064

PACKAGING LENGTH

84

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.064