

Luminaire P2-Flat 15,1W 3000K with detector 8m HF+LUX and emergency IP54

REF. 89161000-153



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and emergency, power 15.1 W, luminous flux of 1608 and color temperature of 3000 K. The duration of the emergency mode is 3 h according to the standard EN 60598-2-22. The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°. The luminosity regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min. Allows interconnection of master/master and master/slave luminaires. The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C. Protection grade IP 54 and IK White, and dimensions: Ø 322 x 68 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

MAXIMUM POWER (W)

400

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053402566

UNITARY PACKAGING GROSS WEIGHT

0.653

PACKAGING LENGTH

410

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.653

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053402566

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.193

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

410

PACKAGING NET WEIGHT

0.653

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

15

PACKAGING WEIGHT UNIT

KGM