

Metal mini tower with 4 heights and 1 side for 8 elements stainless steel Simon 500 Cima

REF. 52510214-036



BASIC INFORMATION

DESCRIPTION

This metal mini-tower 4 heights, 1 side is suitable for 8 elements and manufactured in stainless steel. The product belongs to the Simon 500 Cima series and has dimensions of 298,5 x 221 x 68 mm. The mini-tower is suitable for installing on any floor type, whether raised or concrete. The centre frames of this article include linkable parts that form blocks, allowing separation of the electrical part from the voice and data part for easier maintenance. Complies with the current regulation and is characterized by an extraordinary resistance to high temperatures. For cleaning, it is recommended to use a soft and dry cloth, avoiding abrasive cloths and cleaners containing chlorine. Simon 500 Cima is a collection whose mechanisms to ensure high speed data transmission. They offer an optimal bending radius and more space for the cabling.

FINISH

Metal

MATERIAL

Stainless steel

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using an adaptor)

PACKAGING CONTENTS

Metal mini tower, metal partition wall, ground connection cable, fixing studs, screws and installation manual

ETIM CLASS

EC001941

REMARKS

The frame holders include linkable parts that form blocks, allowing the electrical part to be separated from the voice and data part for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 120° C

NUMBER OF MODULES

8

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using the screws supplied

REMOVAL OF THE FRAME

Only with tool

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing in any floor type, raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053099322

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.941

PRODUCT NET WEIGHT

1.941

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053099322

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

67

PACKAGING WIDTH

168

PACKAGING LENGTH

398

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4.48

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.941

PACKAGING WEIGHT UNIT

KGM

