

Floor trunking 2m and 240x34mm with 4 compartments

REF. TF11193/8



BASIC INFORMATION

DESCRIPTION

The DCS TF11193/8 floor trunking is the most robust solution in the range, ideal for floor installations requiring high resistance. With a 240x34 mm profile, it is made of anodized aluminum and offers IK10 protection, ensuring durability against impacts and constant vehicle passage. Its maximum load capacity of 100 kg/cm² makes it perfect for industrial warehouses, parking lots, and mechanical workshops. The installation is easily carried out on non-combustible floors, ensuring compliance with UNE-EN 50085-1, and allows access to wiring with tools for safe and efficient maintenance.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION

10

KIT AVAILABILITY

No

RAL

7035

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053264188

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

4.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436028067

UNITS CONTAINED PACKAGING

4

PACKAGING HEIGHT

69

PACKAGING WIDTH

319

PACKAGING LENGTH

2030

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

44682330

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

17.7

PACKAGING NET WEIGHT

16.6

PACKAGING WEIGHT UNIT

KGM