

PD-8 PIR+LUX surface DALI-2 Input black IP54

REF. 89212332-138



BASIC INFORMATION

DESCRIPTION

Surface PIR presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360°. The tangential detection range is 8 m, and the radial detection range is 4.5 m.

The luminosity regulation range is 2 - 1000 lux. The detector configuration is done via DALI.

It has a TEACH operating mode. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 12 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

Black finish, protection grade IP 54, and dimensions: Ø 129 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342398

UNITARY PACKAGING GROSS WEIGHT

0.327

PACKAGING LENGTH

135

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.242

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1579500

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053342398

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.327

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

130

PACKAGING NET WEIGHT

0.242

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

90

PACKAGING WEIGHT UNIT

KGM