

Front kit for 2 elements with 1 dimmer rocker,1 USB charger and 1 German socket outlet gloss black Simon 100

REF. 10020209-138



BASIC INFORMATION

DESCRIPTION

This 2-element front kit has 1 adjustable key, 1 USB charger and 1 Schuko plug base. It is black in colour, has a glossy finish and is part of the Simon 100 series. It offers a cut system (1 click), except for the USB that is screw-based. The type of activation it presents is by insertion.

For optimal maintenance of this front kit, designed to occupy two elements, a temperature range should be maintained ranging from 5 to 40° C for operation and a temperature range that ranges from -25 to 50° C for storage . As for the cleaning of the device, it is recommended to use a cloth with soapy water, avoiding products with chemicals such as chlorine.

It is a product designed to be marketed in the EC and follows regulations 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60669 -2-1: 2004 + EN 60669-2-1: 2004 A1: 2009 + EN 60669-2-1: 2004 A12: 2010 * 6 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950-1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3 + ETSI-EN 301489-34 v14.1 * 3 + IEC 60884-1 Ed. 3.2 * 1.

FINISH

Gloss black

COMPATIBILITY

Kit mechanisms Simon 100

MATERIAL

Thermoplastic

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

2 elements

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko,USB

MONOBLOCK

Yes

VERSION

2 elements

INDICATOR FUNCTION

Yes

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical and horizontal

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010*6 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053147702

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.098

PRODUCT NET WEIGHT

0.098

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053147702

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

25.3

PACKAGING WIDTH

155

PACKAGING LENGTH

84

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

329406

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.098

PACKAGING NET WEIGHT

0.098

PACKAGING WEIGHT UNIT

KGM