

**Complete kit with dual opening cover, brush, 8 schuko  
socket outlets and plate for 8 RJ45 connectors black S400  
Indesk Duo**

REF. 46604040-138



## BASIC INFORMATION

### DESCRIPTION

The complete kit integrated into the table with double opening cover and brushes for cable exit, eight schuko socket bases, and plates for 8 RJ45 connectors in black is one of the most demanded products by individuals and professionals of the Simon 400 Indesk Duo series. Its structure is impact-resistant and very durable over time due to the painted steel enclosure, anodized aluminum profile, covers, and fasteners made of self-extinguishing thermoplastic and halogen-free materials, designed to guarantee the prevention of fire hazards. What are its most notable features? Intensity (16 A), voltage (250 V~), insulation resistance (>5 MO at 500 V), connector (Wieland® gst18i with three-pole male aerial with 22 cm patch cord), and dielectric strength (without drilling or contouring with 2000 V at 50 Hz for 1 minute). It is compatible with the rest of the products in the Simon 400 Indesk Duo series.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### RAL

9005

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### CURRENT (A)

16 A

### RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### IP RATING

IP30

### NUMBER OF RJ45 WINDOWS

8

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### SNAP-FIT TYPE

Keystone I, II and Systimax

### FORMAT

Schuko

### NOMINAL VOLTAGE (V~)

250 V~

### NUMBER OF SOCKETS

8 sockets for standard current circuit

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### VERSION

12 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45° and 135°

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208595

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053208595

PACKAGING VOLUME

9990000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

370

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

135

PACKAGING NET WEIGHT

3.4

UNITARY PACKAGING GROSS  
WEIGHT

3.4

PACKAGING LENGTH

200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

3.4