Linear luminaire 6100 BT Mesh 31W 4000K with detector 24GHz 8m HF+LUX and emergency IP65

REF. **89364620-314**



BASIC INFORMATION

DESCRIPTION

Watertight luminaire with integrated HF detector, emergency function and Bluetooth connectivity. Power is 42.4 W, luminous flux is 4525 lm and colour temperature is 4000 K. Emergency mode duration is 3 h in accordance with EN 60598-2-22. Maximum installation height is 4 m, surface-mounted. Detection range is 8 m and detection angle is 360°.
The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The luminaire is configured via a Bluetooth app. Luminaires can be interconnected via Bluetooth mesh.
Supply voltage is 220 - 240 VAC. Operating temperature: -20 - 40 °C.
Protection rating IP 65 and IK 08. Dimensions: 1200 x 90 x 80 mm.
5-year warranty.

For more product information, visit the STEINEL website by clicking here

FINISH

Grey

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

POWER SUPPLY (V~)
220/240 V~

IP RATING
IP65

CONTROL
BT

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053465936

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
3.72

PRODUCT NET WEIGHT
2318

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053465936

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
95

PACKAGING WIDTH
180

PACKAGING LENGTH
1560

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
26676000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3.95

PACKAGING NET WEIGHT
2318

PACKAGING WEIGHT UNIT
KGM