Complete set with 5 schuko socket outlets black S400 Top

REF. **42505000-138**



BASIC INFORMATION

DESCRIPTION

Maximum functionality for the enjoyment of its electrical mechanisms with the kit of desk top full of the collection Simon 400 Top. Designed for 5 socket-outlets ground, with this kit is ideal for working areas, optimises the space in tables and desks. Finished in black, has a compact dimension of 250 x 120 x 80 mm and it is suitable to be installed by flush mounted in furniture, without the need for additional tools. Thanks to these features, the set is integrated into all types of spaces, providing a stylish and minimalist style. Compatible with a voltage of 250 V, and 16 A of intensity, its power supply is connected to figure Wieland gst 18i 3-pole male in-line with patch cord of 22 cm; it also has a insulation resistance > 5 M? at 500 V and dielectric strength of 2000 V at 50H per minute Made of anodised aluminium and thermoplastic self-extinguishing halogen-free, protects the room in case of fire, which prevents the flame spread and toxicity by smoke.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60 C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF SOCKETS
5 sockets for standard current circuit

VERSION
5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053195949

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.85

PRODUCT NET WEIGHT
0.85

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053195949

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
300

PACKAGING WIDTH
125

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3562500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.85

PACKAGING WEIGHT UNIT
KGM