

818.16 1415mm suspended 3000K Opal On-Off CRI80 Black

REF. 81816038-783



BASIC INFORMATION

DESCRIPTION

818 individual linear LED luminaire para carril trifásico con adaptador orientable, with extruded aluminium body y finished in blanco. Length 1415 mm, equipada con diffuser opal y LED module with 3000K con CRI CRI90. Ofrece un luminous flux of 3350 lm con una power of 43W y an efficacy of 79 lm/W. Control On-Off, supply 220-240V, ideal for oficinas, comercios y indoor spaces where functional and efficient lighting is required.

MATERIAL

Aluminium

APPLICATION

General lighting

ETIM CLASS

EC001743

REMARKS

Includes installation accessories.

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

0...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

COLOR TYPE

WW

OPTICS

Opal

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2014/35/UE LVD | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 60598-2-2:2023 used in conjunction IEC 60598-1:2020 | EN IEC 55015:2019 + A11:2020 | EN IEC 55015:2019 + A11:2020 | EN IEC 60598-2-1:2021 | EN IEC 61547:2023 | EN 62493:2015 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN 62717:2017 + A2:2019 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN IEC 63000:201

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053375686

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

4.54

PRODUCT NET WEIGHT

3.965

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053375686

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

145

PACKAGING LENGTH

1430

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

33176000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

4.54

PACKAGING NET WEIGHT

3.965

PACKAGING WEIGHT UNIT

KGM