Switch for blinds 10A 250V~ with 3 positions: up, down and stop white Simon 27 Play

REF. **27333-65**



BASIC INFORMATION

DESCRIPTION

Switch for roller shutters with 10 A current and a power of 250 V~ with three available positions: Raise, lower and stop. Its finish is white in colour and you can find the element in the "Blind control" category of the Simon 27 Play series, its operation is tilting and the type is mechanical latching. As mentioned above, the mechanism is equipped with a control unit position to stop the rise / fall of the blind. Benefit from the best and most innovative electronic functions in addition to imposing the socket of the collection Simon 27 Play in every corner of your home, enjoy decorating is the key premise of the collection, which is why it brings a revolutionary concept that allows you to take the initiative in the decoration of each one of the corners of your home, making the most of each of its features in customization.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000044

REMARKS

Mechanism with centre position to stop the up/down movement of the blinds.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF POSSIBLE ELEMENTS
1 element

INDICATOR FUNCTION
No

CURRENT (A)
10 A

IP RATING
IP20

LATCH TYPE
Mechanical

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Pivoting

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252017

UNITARY PACKAGING HEIGHT
22.8

UNITARY PACKAGING WIDTH
39.2

UNITARY PACKAGING LENGTH
46

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.026

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.035

PRODUCT NET WEIGHT
0.035

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053080832

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
50

PACKAGING WIDTH
105.4

PACKAGING LENGTH
220

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.159

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.336

PACKAGING NET WEIGHT
0.35

PACKAGING WEIGHT UNIT
KGM