

Waterproof linear luminaire BT Mesh 31W 4000K with detector 10m HF+LUX and emergency IP65

REF. 89362600-314



BASIC INFORMATION

DESCRIPTION

Watertight fixture with integrated HF detector, with emergency and Bluetooth connectivity. The power is 31 W, the luminous flux is 4250 lm, and the color temperature is 4000 K. The emergency mode duration is 3 h according to standard EN 60598-2-22. The maximum installation height is 4 m, and the installation is surface-mounted. The detection range is 10 m, and the detection angle is 360°. The light regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The fixture configuration is done through a Bluetooth application. Possibility of interconnection between fixtures via Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection rating IP 65 and IK 07. Dimensions: 1370 x 87 x 58 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP65

IK CLASSIFICATION

07

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401576

UNITARY PACKAGING GROSS WEIGHT

2.28

PACKAGING LENGTH

1423

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.68

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053401576

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.28

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

93

PACKAGING NET WEIGHT

1.68

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

77

PACKAGING WEIGHT UNIT

KGM