

Downlight 800.22 Black 24W 4000K DALI2

REF. 80022338-684



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

2400 lm/24W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Closed

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

24°

POWER (W)

24W

COLOR TEMPERATURE (K)

3000K

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CONTROL

DALI2

LIGHTING EFFICIENCY (LM/W)

105 lm/W

COS Φ

0.95

LUMENS (LM)

2400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

115

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053308004

PACKAGING VOLUME

6054750

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

0.868

UNITARY PACKAGING GROSS WEIGHT

0.678

PACKAGING WIDTH

195

PACKAGING NET WEIGHT

0.678

PRODUCT NET WEIGHT

0.678

PACKAGING LENGTH

230

PACKAGING WEIGHT UNIT

KGM