Floor trunking 2m and 240x34mm with 4 compartments

REF. **TF11193/8**



BASIC INFORMATION

DESCRIPTION

The DCS TF11193/8 floor trunking is the most robust solution in the range, ideal for floor installations requiring high resistance. With a 240x34 mm profile, it is made of anodized aluminum and offers IK10 protection, ensuring durability against impacts and constant vehicle passage. Its maximum load capacity of 100 kg/cm² makes it perfect for industrial warehouses, parking lots, and mechanical workshops. The installation is easily carried out on non-combustible floors, ensuring compliance with UNE-EN 50085-1, and allows access to wiring with tools for safe and efficient maintenance.

FINISH	MATERIAL	ETIM CLASS
Aluminium	Aluminium	EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION
10

KIT AVAILABILITY
No

RAL
7035

IP RATING
IP4X

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053264188

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
4.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436028067

UNITS CONTAINED PACKAGING
4

PACKAGING HEIGHT
69

PACKAGING WIDTH
319

PACKAGING LENGTH
2030

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
44682330

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
17.7

PACKAGING NET WEIGHT
16.6

PACKAGING WEIGHT UNIT
KGM