

Downlight 725.23 Flush mount NW General White

REF. 72523030-984



BASIC INFORMATION

DESCRIPTION

Simon is updated constantly, and performs tests of all kinds, both of its own and external laboratories R + D + i. In this way, it complies with the most demanding international standards, and can offer all kinds of solutions to the professionals and the design of the installations. The Downlight 725 is optimal for creating uniform lighting with high visual comfort. It is the most appropriate site in transit areas, corridors, general office lighting and commercial establishments. Its adjustable system offers appropriate light in each situation. Light continuous, without flashes that prevent visual fatigue. This is in this case the luminaire Downlight 725.23 recessed. Colour 3900 K NW Advance. General. Category A. While 30,000 h at 25 ° C, 14 W. 100-240 V 50 / 60 Hz. System of switching on ON-OFF and possibility of adjustment. Weight 0.5 kg Colour White. 165x51 mm dimensions for flush mounting.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1300 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

93 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.504

PRODUCT NET WEIGHT

0.504

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116807

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

195

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.042

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.504

PACKAGING WEIGHT UNIT

KGM