Customisable set with 4 schuko socket outlets and 2 empty elements white S400 Top

REF. **42604000-130**



BASIC INFORMATION

DESCRIPTION

With a modern design and minimalist and finishes in white, the kit table-top customizable of Simon 400 Top not only provides a style modern and functional, but also guarantees maximum functionality and innovation for connectivity in your office or working area. With 4 Schuko socket outlets and 2 empty elements, you can personalize it by selecting the functions that requires its environment. Designed for flush installation using clamps pages, this kit is enlaza to a connector figure Wieland gst 18 i, with 3-pole male and patch cord of 22 cm compatible with a voltage of 250 V of power and 16 A of intensity, has a dielectric strength, with no holes or contours, 2000 V at 50H during 1 minute, and insulation resistance > 5 M? at 500 V. Made of anodised aluminium and thermoplastic self-extinguishing halogen-free, protects the room in case of fire, which prevents the flame spread and toxicity by smoke. Security, innovation and the maximum functionality for its work area with this kit for table-top Simon 400 Top.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

NUMBER OF POSSIBLE ELEMENTS
2

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9016

NUMBER OF REAR ENTRANCES
2

NUMBER OF SOCKETS
4 sockets for standard current circuit

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

REMOVAL OF THE PLATE
Only with tool

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196106

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.05

PRODUCT NET WEIGHT
1.05

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196106

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
330

PACKAGING WIDTH
125

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3918750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.05

PACKAGING WEIGHT UNIT
KGM