

Waterproof luminaire 780 IP65 4000 K 600 1-10 V

REF. 78030133-884



BASIC INFORMATION

DESCRIPTION

The 780 waterproof luminaire, made with an extruded PC body, is perfect for lighting car parks, industries, underpasses, storage areas, humid spaces, etc. Its LED technology allows it to switch on instantly and avoid flickering. The luminaire is IP65 and IK08 rated and comes in 3 different sizes and versions with 1-10 V / DALI dimming.

APPLICATION

Car park lighting, Industrial lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

2100 lm/20W

IK CLASSIFICATION

08

ELECTRICAL CLASS

Type 2

OPTICS

General

IP RATING

IP65

L70 (°C)

50,000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

OPERATING TEMPERATURE RANGE (°C)

-20 - 35 °C

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

20 W

POWER SUPPLY (V~)

220/240 V~

COLOR TYPE

NW

SERVICE LIFE

50.000 h

COLOR TEMPERATURE (K)

4000 K

LIGHTING EFFICIENCY (LM/W)

105 lm/W

CONTROL

1-10 V

LUMENS (LM)

2100 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface-mounted / Wall /
Suspended

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053217108

PACKAGING VOLUME

3830400

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

950

PACKAGING GROSS WEIGHT

0.726

UNITARY PACKAGING GROSS WEIGHT

0.726

PACKAGING WIDTH

64

PACKAGING NET WEIGHT

0.54

PRODUCT NET WEIGHT

0.54

PACKAGING LENGTH

63

PACKAGING WEIGHT UNIT

KGM