

Modular luminaire 720 Advance M4 120x30 Low Glare WW

REF. 72061040-683



BASIC INFORMATION

DESCRIPTION

With the luminaire 720 modular Advance M4 of the collection Simon you will get the perfect balance between the highest quality lighting and a greater savings. With a dimension of 120 x 30 mm and control of anti-deslumbramiento LowGlare, this luminaire provides a warm light (3000K) with 3200 lm for WW y a consumption of 28 W. Composed of multiple low power LEDs, has a service life of 100,000 hours for the L70 at 25 ° C and up to 40,000 hours for the L90. With control of switching on on-off included, it is compatible with a voltage of 230 V AC power and 50-60 Hz frequency. Designed for installation both flush mounted and surface-mounted, in false ceiling and hardware view, the set adapts to all types of spaces, environments and decorative styles.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

114 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3200 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191699

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.58

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053191699

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM