

Voice and data angled plate without dust cover for 1 element for 2 RJ45 connectors black Simon K45

REF. KB080/14



BASIC INFORMATION

DESCRIPTION

The series Simon K45 presents the plate of voice and data plate without dust cover with 1 element for 2 RJ45 category 5e FTP connectors, suitable for surface or flush mounting. It measures 45x45 mm and a thickness of 25 mm with, in addition to a perfect finishes in black, in addition, it is manufactured with thermoplastic components halogen-free, guaranteeing no flame spread, so you can notional in the event of a fire, along with a very low toxicity if any smoke. If you are looking for combining the voice and data plate in vertical enclosures, it would be necessary to use the 90° positioner in order to be able to guide the piece in vertical position. The collection Simon K45 presents the best solutions for those who are looking for the best workplace solutions for your home, and that is that the commitment Simon is to offer the safest and innovative on the market.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Angled voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

RJ45

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

IP RATING

IP20

RAL

7021

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

According to combined MD module

DUST PROTECTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

According to combined MD module

DUST SHUTTER

No

NUMBER OF MODULES

Half

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.012

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436036307

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.24

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.24

UNITARY PACKAGING GROSS WEIGHT

0.012

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195